

Equipped with additional tools, a Brokk becomes even more profitable for your business. Grapples, scabblers, buckets, drills and other devices greatly expand the machine's efficiency and versatility. Here's our wide and ever-expanding range of original Brokk attachments:



SB302



## ■ BREAKERS

|                | Hitting power* | Blows/min  | Weight          | Made for             |
|----------------|----------------|------------|-----------------|----------------------|
| <b>SB 52</b>   | 101 J/Nm       | 720 – 1680 | 60 kg/132 lb    | Brokk 50             |
| <b>SB 152</b>  | 254 J/Nm       | 780 – 1920 | 142 kg/315 lb   | Brokk 100, 160       |
| <b>SB 202</b>  | 406 J/Nm       | 840 – 1800 | 212 kg/470 lb   | Brokk 160, 180       |
| <b>SB 302</b>  | 610 J/Nm       | 600 – 1410 | 310 kg/685 lb   | Brokk 260, 330D, 400 |
| <b>SB 452</b>  | 855 J/Nm       | 540 – 1260 | 450 kg/990 lb   | Brokk 330D, 400      |
| <b>SB 552</b>  | 1048 J/Nm      | 660 – 1140 | 535 kg/1177 lb  | Brokk 400            |
| <b>MB 1000</b> | 2033 J/Nm      | 350 – 750  | 1295 kg/2850 lb | Brokk 800            |

\*Actual output, impact energy class (Joule/Nm)

A variety of chisels and tools can be fitted to the breakers. Other breaker brands can also be used on Brokk machines. Contact your local Brokk dealer or Brokk AB for information.

PTA-09



## ■ SIDE ANGLING DEVICE

|                 | Angle | Weight         | Made for         |
|-----------------|-------|----------------|------------------|
| <b>PTA-04,5</b> | ±60°  | 180 kg/407 lb  | SB 152/Brokk 100 |
| <b>PTA-06</b>   | ±70°  | 215 kg/473 lb  | SB 152/Brokk 160 |
| <b>PTA-07</b>   | ±70°  | 330 kg/725 lb  | SB 202/Brokk 260 |
| <b>PTA-09</b>   | ±55°  | 555 kg/1220 lb | SB 302/Brokk 400 |

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)



CC520



## CONCRETE CRUSHERS\*\*

|               | Jaw opening    | Rebars        | Crushing force           | Weight              | Made for           |
|---------------|----------------|---------------|--------------------------|---------------------|--------------------|
| <b>CC260</b>  | 250 mm/10 in   | Ø20 mm/0.8 in | 220 kN/22 t/<br>50 Klb   | 76 kg/<br>160 lb    | Brokk 50           |
| <b>CC320</b>  | 316 mm/12.4 in | Ø20 mm/0.8 in | 320 kN/32,6 t/<br>792Klb | 150 kg/<br>330 lb   | Brokk 100          |
| <b>CC420*</b> | 420 mm/16.5 in | Ø28 mm/1.1 in | 382 kN/38,2 t/<br>85 Klb | 265 kg/<br>585 lb   | Brokk 160          |
| <b>CC520*</b> | 540 mm/21.3 in | Ø28 mm/1.1 in | 466 kN/48 t/<br>105 Klb  | 410 kg/<br>900 lb   | Brokk 260,<br>330D |
| <b>CC700*</b> | 680 mm/27 in   | Ø28 mm/1.1 in | 680 kN/69 t/<br>162 Klb  | 595 kg/<br>1,310 lb | Brokk 400, 800     |

\*Option pulverizing pads

\*\*Free rotation



## METAL SHEARS\*

|                | Cutting force         | Jaw opening    | Weight          | Made for        |
|----------------|-----------------------|----------------|-----------------|-----------------|
| <b>HCS6</b>    | 169 kN/17 t/37 Klb    | 320 mm/12.6 in | 55 kg/120 lb    | Brokk 50, 100   |
| <b>HCS7</b>    | 312 kN/31 t/69 Klb    | 350 mm/13.8 in | 123 kg/270 lb   | Brokk 100, 160  |
| <b>CC420S</b>  | 740 kN/75.4 t/166 Klb | 145 mm/5.7 in  | 310 kg/680 lb   | Brokk 160, 260  |
| <b>CC700S</b>  | 1772 kN/181 t/398 Klb | 271 mm/10.5 in | 690 kg/1520 lb  | Brokk 400, 800  |
| <b>BMS 100</b> | 1020 kN/102 t/225 Klb | 185 mm/7.3 in  | 385 kg/850 lb   | Brokk 160, 260  |
| <b>BMS 140</b> | 1380 kN/138 t/304 Klb | 245 mm/9.6 in  | 645 kg/1420 lb  | Brokk 330D, 400 |
| <b>BMS 250</b> | 2500 kN/250 t/550 Klb | 395 mm/15.5 in | 1205 kg/2650 lb | Brokk 800       |

\*Requires one extra hydraulic function  
Rotator with continuous rotation



BMS 250



## BUCKETS\*

| Volume           | Width         | Weight         | Made for             |
|------------------|---------------|----------------|----------------------|
| 20 l/0.7 cu ft   | 330 mm/12 in  | 20 kg/44 lb    | Brokk 50             |
| 60 l/2.1 cu ft   | 520 mm/20 in  | 61 kg/134 lb   | Brokk 100            |
| 80 l/2.8 cu ft   | 690 mm/27 in  | 76 kg/167 lb   | Brokk 160            |
| 250 l/8.8 cu ft  | 960 mm/38 in  | 195 kg/430 lb  | Brokk 260, 330D, 400 |
| 500 l/17.6 cu ft | 1200 mm/47 in | 600 kg/1300 lb | Brokk 800            |

\*See load diagram for each Brokk machine

250 l



All weights are relate operational tool (incl: mounting plate, hoses, oil etc)



CO5HPX




## CLAMSHELL BUCKETS\*

|                  | Volume           | Opening range | Width        | Weight         | Made for   |
|------------------|------------------|---------------|--------------|----------------|------------|
| <b>CO2H-25</b>   | 25 l/0.9 cu ft   | 667 mm/26 in  | 250 mm/10 in | 110 kg/240 lb  | Brokk 100  |
| <b>CO3H-35</b>   | 65 l/2.3 cu ft   | 879 mm/35 in  | 350 mm/14 in | 175 kg/385 lb  | Brokk 160  |
| <b>CO5H-40</b>   | 115 l/4.1 cu ft  | 1090 mm/43 in | 400 mm/16 in | 210 kg/460 lb  | Brokk 260  |
| <b>CO5HPX-40</b> | 115 l/4.1 cu ft  | 1112 mm/44 in | 400 mm/16 in | 340 kg/750 lb  | Brokk 330D |
| <b>CO5HPX-60</b> | 170 l/6.1 cu ft  | 1112 mm/44 in | 600 mm/24 in | 375 kg/825 lb  | Brokk 400  |
| <b>CO8HPX-80</b> | 300 l/10.6 cu ft | 1250 mm/50 in | 800 mm/31 in | 580 kg/1275 lb | Brokk 800  |

\*See load diagram for each Brokk machine  
 Rotator with continuous rotation  
 Requires one extra hydraulic function



AO5H-40



## MULTI PURPOSE GRAPPLES\*

|                            | Volume          | Opening range | Width         | Weight         | Made for        |
|----------------------------|-----------------|---------------|---------------|----------------|-----------------|
| <b>AO2H-30</b>             | 35 l/1.2 cu ft  | 760 mm/30 in  | 300 mm/12 in  | 133 kg/295 lb  | Brokk 100       |
| <b>AO2H-30</b>             | 35 l/1.2 cu ft  | 760 mm/30 in  | 300 mm/12 in  | 144 kg/320 lb  | Brokk 160       |
| <b>AO3H-40</b>             | 70 l/2.5 cu ft  | 1474 mm/58 in | 390 mm/15 in  | 265 kg/585 lb  | Brokk 260       |
| <b>AO5H-40</b>             | 70 l/2.5 cu ft  | 1474 mm/58 in | 390 mm/15 in  | 320 kg/705 lb  | Brokk 330D      |
| <b>AO5HPX-40</b>           | 100 l/3.6 cu ft | 1399 mm/55 in | 400 mm/16 in  | 375 kg/825 lb  | Brokk 400       |
| <b>AO9HPX-50</b>           | 200 l/7.1 cu ft | 1695 mm/66 in | 500 mm/20 in  | 675 kg/1490 lb | Brokk 800       |
| <b>Orange Peel Grapple</b> |                 |               |               |                |                 |
| <b>KM651-4 180</b>         | 180 l/6.4 cu ft | 1450 mm/57 in | 1070 mm/42 in | 520 kg/1150 lb | Brokk 330D, 400 |
| <b>KM651-4 250</b>         | 250 l/8.8 cu ft | 1550 mm/61 in | 1285 mm/51 in | 870 kg/1920 lb | Brokk 800       |

\*See load diagram for each Brokk machine  
 Requires one extra hydraulic function  
 Rotator with continuous rotation



KM650



G50



## SORTING & DEMOLITION GRAPPLES\*

|                  | Jaw opening   | Weight         | Made for        |
|------------------|---------------|----------------|-----------------|
| <b>G30</b>       | 300 mm/12 in  | 42 kg/92 lb    | Brokk 50        |
| <b>G50</b>       | 500 mm/20 in  | 133 kg/295 lb  | Brokk 100       |
| <b>G50</b>       | 500 mm/20 in  | 145 kg/320 lb  | Brokk 160       |
| <b>D02H-30</b>   | 792 mm/31 in  | 133 kg/295 lb  | Brokk 100       |
| <b>D02H-30</b>   | 792 mm/31 in  | 145 kg/320 lb  | Brokk 160       |
| <b>D03HPX-40</b> | 975 mm/38 in  | 310 kg/680 lb  | Brokk 260, 330D |
| <b>D05HPX-50</b> | 1135 mm/45 in | 375 kg/825 lb  | Brokk 400       |
| <b>D09HPX-60</b> | 1400 mm/56 in | 595 kg/1310 lb | Brokk 800       |

\*See load diagram for each Brokk machine  
 Requires one extra hydraulic function  
 Rotator with continuous rotation

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)

WS 15



## SCABLERS

|               | Cutting depth**  | Width        | Weight            | Made for             |
|---------------|------------------|--------------|-------------------|----------------------|
| <b>RT 15*</b> | 0-10 mm/0-0.4 in | 203 mm/8 in  | 82 kg/180 lb      | Brokk 100, 160       |
| <b>ER 50</b>  | 0-30 mm/0-1.2 in | 480 mm/19 in | 115 kg/250 lb     | Brokk 100, 160       |
| <b>WS15</b>   | 0-62 mm/0-2.4 in | 557 mm/22 in | 330 kg/725 lb     | Brokk 160, 260, 330D |
| <b>ER 100</b> | 0-65 mm/0-2.6 in | 550 mm/22 in | 300 kg/660 lb     | Brokk 160, 260, 330D |
| <b>WS30</b>   | 0-89 mm/0-3.5 in | 678 mm/27 in | 490 kg/1,075 lb   | Brokk 330D, 400      |
| <b>ER 250</b> | 0-80 mm/0-3.2 in | 620 mm/24 in | 520 kg/1,150 lb   | Brokk 330D, 400      |
| <b>ER 600</b> | 0-100 mm/0-4 in  | 780 mm/31 in | 1,120 kg/2,460 lb | Brokk 800            |
| <b>WS45</b>   | 0-100 mm/0-4 in  | 655 mm/26 in | 1,070 kg/2350 lb  | Brokk 800            |

\*Also available with cover and suction

\*\*Data depending on concrete quality

BCP250



## PLANERS

|                  | Cutting depth    | Width          | Weight        | Made for             |
|------------------|------------------|----------------|---------------|----------------------|
| <b>BCP 250*</b>  | 0-6 mm/0-0.25 in | 265 mm/10.4 in | 220 kg/485 lb | Brokk 100, 160       |
| <b>BCP 350*</b>  | 0-6 mm/0-0.25 in | 335 mm/13.2 in | 250 kg/550 lb | Brokk 260, 330D, 400 |
| <b>PLB 200**</b> | 0-50 mm/0-2 in   | 200 mm/7.8 in  | 220 kg/485 lb | Brokk 160, 180       |
| <b>PLB 300*</b>  | 0-50 mm/0-2 in   | 300 mm/11.8 in | 290 kg/640 lb | Brokk 260, 330D, 400 |

\*Available with cover and suction

\*\*Available with cover, suction only on special request

PLB 300



MMB260



## DRILLING EQUIPMENT



|  | Length             | Bore depth                        | Drill diam. (Std)***     | Water or airflushing   | Weight             | Made for                |
|--|--------------------|-----------------------------------|--------------------------|--|--------------------|-------------------------|
| <b>BSD-80**</b><br>(concrete)                | 1760 mm/<br>70 in  | 600 mm/23 in*<br>max 2 m/80 in    | 24-51 mm/<br>1.2 - 2 in  | 0.4 m <sup>3</sup> /min<br>at 5-16 bar<br>or 10 l/min<br>at 4-16 bar | 205 kg/<br>450 lb  | Brokk 100               |
| <b>MMB260-180****</b><br>(concrete and rock) | 2900 mm/<br>115 in | 1600 mm/63 in*<br>max 10 m/395 in | 33-76 mm/<br>1.3 - 3 in  | 0.5 m <sup>3</sup> /min<br>at 5-20 bar<br>or 25 l/min<br>at 4-20 bar | 415 kg/<br>915 lb  | Brokk 160               |
| <b>MMB260-240****</b><br>(concrete and rock) | 3500 mm/<br>138 in | 2200 mm/87 in*<br>max 10 m/395 in | 33-76 mm/<br>1.3 - 3 in  | 0.5 m <sup>3</sup> /min at<br>5-20 bar<br>or 25 l/min<br>at 4-20 bar | 432 kg/<br>952 lb  | Brokk 260,<br>330D, 400 |
| <b>HEB350-240****</b><br>(concrete and rock) | 3590 mm/<br>141 in | 2200 mm/87 in*<br>max 20 m/790 in | 41-102 mm/<br>1.6 - 4 in | 0.5 m <sup>3</sup> /min<br>at 5-20 bar<br>or 25 l/min<br>at 4-20 bar | 760 kg/<br>1675 lb | Brokk 400,<br>800       |

\*Per stroke


\*\*Requires one extra hydraulic function

\*\*\*Additional drill diameter on request

\*\*\*\*Requires drainage hose, 24 v cable kit, electric hang up function kit, counter weight in some occasions

All weights are relate operational tool (incl: mounting plate, hoses, oil etc)

Brokk Beam Grapple



## TUNNEL AND MINING EQUIPMENT

|                             | Jaw opening   | Beam weight*   | Weight        | Made for                  |
|-----------------------------|---------------|----------------|---------------|---------------------------|
| <b>Brokk Beam Grapple**</b> | 240 mm/9.5 in | 500 kg/1100 lb | 320 kg/705 lb | Brokk 260, 330D, 400, 800 |



Brokk Shot Crete

|                           | Concrete hose (di) | Gunning pressure   | Air pressure              | Weight        | Made for                  |
|---------------------------|--------------------|--------------------|---------------------------|---------------|---------------------------|
| <b>Brokk Shot Crete**</b> | 45 mm/<br>1.77 in  | 65 bar/<br>6.5 mpa | 0.1-0.2 m³/<br>at 3-5 bar | 180 kg/400 lb | Brokk 260, 330D, 400, 800 |

\*See load diagram for each Brokk machine

\*\*Requires two extra hydraulic functions

Cut Off Saw



## CUT OFF SAW\*

|                        | Saw disk diameter**               | Cutting depth***                 | Weight****        | Made for                  |
|------------------------|-----------------------------------|----------------------------------|-------------------|---------------------------|
| <b>BCS 8</b>           | 355 or 400 mm/<br>14 or 15.75 in  | 150 or 170 mm/<br>5.9 or 6.7 in  | 70 kg/<br>155 lb  | Brokk 50                  |
| <b>BCS10</b>           | 355 or 400 mm/<br>14 or 15.75 in  | 150 or 170 mm/<br>5.9 or 6.7 in  | 85 kg/<br>190 lb  | Brokk 100, 160            |
| <b>BCS 25</b><br>***** | 600 or 800 mm/<br>23.5 or 31.5 in | 160 or 260 mm/<br>6.3 or 10.2 in | 250 kg/<br>550 lb | Brokk 160, 260            |
| <b>BCS 35</b><br>***** | 600 or 800 mm/<br>23.5 or 31.5 in | 160 or 260 mm/<br>6.3 or 10.2 in | 260 kg/<br>575 lb | Brokk 260, 330D, 400, 800 |

\*Requires one extra hydraulic function

\*\*Different saw disks available depending on material

\*\*\*With new saw disk

\*\*\*\*Depending on machine model

\*\*\*\*\*Requires drainage hose